

Revised Report on the Algorithmic Language ALGOL 60

PETER NAUR (*Editor*)

J. W. BACKUS	C. KATZ	H. RUTISHAUSER	J. H. WEGSTEIN
E. L. BAUER	J. MCCARTHY	K. SAMELSON	A. VAN WIJNGAARDEN
J. GREEN	A. J. PERLIS	B. VAUQUOIS	M. WOODGER

Dedicated to the Memory of WILLIAM TURANSKI

SUMMARY

The report gives a complete defining description of the international algorithmic language ALGOL 60. This is a language suitable for expressing a large class of numerical processes in a form sufficiently concise for direct automatic translation into the language of programmed automatic computers.

The introduction contains an account of the preparatory work leading up to the final conference, where the language was defined. In addition, the notions, reference language, publication language and hardware representations are explained.

In the first chapter, a survey of the basic constituents and features of the language is given, and the formal notation, by which the syntactic structure is defined, is explained.

The second chapter lists all the basic symbols, and the syntactic units known as identifiers, numbers and strings are defined. Further, some important notions such as quantity and value are defined.

The third chapter explains the rules for forming expressions and the meaning of these expressions. Three different types of expressions exist: arithmetic, Boolean (logical) and designational.

The fourth chapter describes the operational units of the language, known as statements. The basic statements are: assignment statements (evaluation of a formula), go to statements (explicit break of the sequence of execution of statements), dummy statements, and procedure statements (call for execution of a closed process, defined by a procedure declaration). The formation of more complex structures, having statement character, is explained. These include: conditional statements, for statements, compound statements, and blocks.

In the fifth chapter, the units known as declarations, serving for defining permanent properties of the units entering into a process described in the language, are defined.

The report ends with two detailed examples of the use of the language and an alphabetic index of definitions.

CONTENTS

- INTRODUCTION
- 1. STRUCTURE OF THE LANGUAGE
 - 1.1. Formalism for syntactic description
- 2. BASIC SYMBOLS, IDENTIFIERS, NUMBERS, AND STRINGS.
 - BASIC CONCEPTS.
 - 2.1. Letters
 - 2.2. Digits, Logical values.
 - 2.3. Delimiters
 - 2.4. Identifiers
 - 2.5. Numbers
 - 2.6. Strings
 - 2.7. Quantities, kinds and scopes
 - 2.8. Values and types
- 3. EXPRESSIONS
 - 3.1. Variables
 - 3.2. Function designators
 - 3.3. Arithmetic expressions
 - 3.4. Boolean expressions
 - 3.5. Designational expressions
- 4. STATEMENTS
 - 4.1. Compound statements and blocks
 - 4.2. Assignment statements
 - 4.3. Go to statements
 - 4.4. Dummy statements
 - 4.5. Conditional statements
 - 4.6. For statements
 - 4.7. Procedure statements
- 5. DECLARATIONS
 - 5.1. Type declarations
 - 5.2. Array declarations
 - 5.3. Switch declarations
 - 5.4. Procedure declarations

EXAMPLES OF PROCEDURE DECLARATIONS
ALPHABETIC INDEX OF DEFINITIONS OF CONCEPTS AND
SYNTACTIC UNITS

This report was published simultaneously in the Communications of the ACM, 6, No. 1 (1963), 1-17, the Numerische Mathematik, and the Computer Journal.

INTRODUCTION

Background

After the publication of a preliminary report on the algorithmic language ALGOL,¹ as prepared at a conference in Zürich in 1958, much interest in the ALGOL language developed.

As a result of an informal meeting held at Mainz in November 1958, about forty interested persons from several European countries held an ALGOL implementation conference in Copenhagen in February 1959. A "hardware group" was formed for working cooperatively right down to the level of the paper tape code. This conference also led to the publication by Regnecentralen, Copenhagen, of an *ALGOL Bulletin*, edited by Peter Naur, which served as a forum for further discussion. During the June 1959 ICIP Conference in Paris several meetings, both formal and informal ones, were held. These meetings revealed some misunderstandings as to the intent of the group which was primarily responsible for the formulation of the language, but at the same time made it clear that there exists a wide appreciation of the effort involved. As a result of the discussions it was decided to hold an international meeting in January 1960 for improving the ALGOL language and preparing a final report. At a European ALGOL Conference in Paris in November 1959 which was attended by about fifty people, seven European representatives were selected to attend the January 1960 Conference, and they represent the following organizations: Association Française de Calcul, British Computer Society, Gesellschaft für Angewandte Mathematik und Mechanik, and Nederlands Rekenmachine Genootschap. The seven representatives held a final preparatory meeting at Mainz in December 1959.

Meanwhile, in the United States, anyone who wished to suggest changes or corrections to ALGOL was requested to send his comments to the *Communications of the ACM*, where they were published. These comments then became the basis of consideration for changes in the ALGOL language. Both the SHARE and USE organizations established ALGOL working groups, and both organizations were represented on the ACM Committee on Programming Languages. The ACM Committee met in Washington in November 1959 and considered all comments on ALGOL that had been sent to the *ACM Communications*. Also, seven representatives were selected to attend the January 1960 international conference. These seven representatives held a final preparatory meeting in Boston in December 1959.

January 1960 Conference

The thirteen representatives,² from Denmark, England, France, Germany, Holland, Switzerland, and the United States, conferred in Paris from January 11 to 16, 1960.

Prior to this meeting a completely new draft report was worked out from the preliminary report and the recommendations of the preparatory meetings by Peter Naur

and the conference adopted this new form as the basis for its report. The Conference then proceeded to work for agreement on each item of the report. The present report represents the union of the Committee's concepts and the intersection of its agreements.

April 1962 Conference [Edited by M. Woodger]

A meeting of some of the authors of ALGOL 60 was held on April 2-3, 1962 in Rome, Italy, through the facilities and courtesy of the International Computation Centre. The following were present:

<i>Authors</i>	<i>Editors</i>	<i>Observer</i>
F. L. Bauer	M. Paul	W. L. van der Poel
J. Green	R. Franciotti	(Chairman, IFIP
C. Katz	P. Z. Ingerman	TC 2.1 Working
R. Kogon		Group ALGOL)
(representing J. W. Backus)		
P. Naur		
K. Samuelson	G. Seegenmüller	
J. H. Wegstein	R. E. Urean	
A. van Wijngaarden		
M. Woodger	P. Landin	

The purpose of the meeting was to correct known errors in, attempt to eliminate apparent ambiguities in, and otherwise clarify the ALGOL 60 Report. Extensions to the language were not considered at the meeting. Various proposals for correction and clarification that were submitted by interested parties in response to the Questionnaire in *ALGOL Bulletin* No. 11 were used as a guide.

This report* constitutes a supplement to the ALGOL 60 Report which should resolve a number of difficulties therein. Not all of the questions raised concerning the original report could be resolved. Rather than risk hastily drawn conclusions on a number of subtle points, which might create new ambiguities, the committee decided to report only those points which they unanimously felt could be stated in clear and unambiguous fashion.

Questions concerned with the following areas are left for further consideration by Working Group 2.1 of IFIP, in the expectation that current work on advanced pro-

* Error's Note. The present edition follows the text which was approved by the Council of IFIP. Although it is not clear from the Introduction, the present version is the original report of the January 1960 conference modified according to the agreements reached during the April 1962 conference. Thus the report mentioned here is incorporated in the present version. The modifications touch the original report in the following sections: Changes of text: 1 with footnote; 2.1 footnote; 2.3; 2.7; 3.3.3; 3.3.4.2; 4.1.3; 4.2.3; 4.2.4; 4.3.1; 4.7.3; 4.7.3.1; 4.7.3.3; 4.7.5.1; 4.7.5.4; 4.7.6; 5; 5.3.3; 5.3.5; 5.4.3; 5.4.4; 5.4.5. Changes of syntax: 3.4.1; 4.1.1; 4.2.1; 4.5.1.1

¹ Preliminary report—International Algorithmic Language, *Comm. ACM* 1, 12 (1958), 8.

² Report on the Algorithmic Language ALGOL by the ACM Committee on Programming Languages and the GAMM Committee on Programming, edited by A. J. Perlis and K. Samuelson, *Nouv. Math.* 1 (1959), 41-60.

³ William Turanski of the American group was killed by an automobile just prior to the January 1960 Conference.

gramming languages will lead to better resolution:

1. Side effects of functions
2. The call by name concept
3. **own**: static or dynamic
4. For statement: static or dynamic
5. Conflict between specification and declaration

The authors of the ALGOL 60 Report present at the Rome Conference, being aware of the formation of a Working Group on ALGOL by IFIP, accepted that any collective responsibility which they might have with respect to the development, specification and refinement of the ALGOL language will from now on be transferred to that body.

This report has been reviewed by IFIP TC 2 on Programming Languages in August 1962 and has been approved by the Council of the International Federation for Information Processing.

As with the preliminary ALGOL report, three different levels of language are recognized, namely a Reference Language, a Publication Language and several Hardware Representations.

REFERENCE LANGUAGE

1. It is the working language of the committee.
2. It is the defining language.
3. The characters are determined by ease of mutual understanding and not by any computer limitations, coders notation, or pure mathematical notation.
4. It is the basic reference and guide for compiler builders.
5. It is the guide for all hardware representations.
6. It is the guide for transliterating from publication language to any locally appropriate hardware representations.

DESCRIPTION OF THE REFERENCE LANGUAGE

Was sich überhaupt sagen lässt, lässt
sich klar sagen; und wovon man nicht
reden kann, darüber muss man schweigen.
LUDWIG WITGENSTEIN.

1. Structure of the Language

As stated in the introduction, the algorithmic language has three different kinds of representations—reference, hardware, and publication—and the development described in the sequel is in terms of the reference representation. This means that all objects defined within the language are represented by a given set of symbols—and it is only in the choice of symbols that the other two representations may differ. Structure and content must be the same for all representations.

The purpose of the algorithmic language is to describe computational processes. The basic concept used for the description of calculating rules is the well-known arithmetic expression containing as constituents numbers, variables, and functions. From such expressions are compounded, by applying rules of arithmetic composition,

7. The main publications of the ALGOL language itself will use the reference representation.

PUBLICATION LANGUAGE

1. The publication language admits variations of the reference language according to usage of printing and handwriting (e.g., subscripts, spaces, exponents, Greek letters).
2. It is used for stating and communicating processes.
3. The characters to be used may be different in different countries, but univocal correspondence with reference representation must be secured.

HARDWARE REPRESENTATIONS

1. Each one of these is a condensation of the reference language enforced by the limited number of characters on standard input equipment.
2. Each one of these uses the character set of a particular computer and is the language accepted by a translator for that computer.
3. Each one of these must be accompanied by a special set of rules for transliterating from Publication or Reference language.

For transliteration between the reference language and a language suitable for publications, among others, the following rules are recommended.

<i>Reference Language</i>	<i>Publication Language</i>
Subscript bracket []	Lowering of the line between the brackets and removal of the brackets
Exponentiation ^	Raising of the exponent
Parentheses ()	Any form of parentheses, brackets, braces
Basis of ten 10^x	Raising of the ten and of the following integral number, inserting of the intended multiplication sign

self-contained units of the language—explicit formulae—called assignment statements.

To show the flow of computational processes, certain nonarithmetic statements and statement clauses are added which may describe, e.g., alternatives, or iterative repetitions of computing statements. Since it is necessary for the function of these statements that one statement refer to another, statements may be provided with labels. A sequence of statements may be enclosed between the statement brackets **begin** and **end** to form a compound statement.

Statements are supported by declarations which are not themselves computing instructions but inform the translator of the existence and certain properties of objects appearing in statements, such as the class of numbers taken on as values by a variable, the dimension of an

REVISED ALGOL 60

array of numbers, or even the set of rules defining a function. A sequence of declarations followed by a sequence of statements and enclosed between **begin** and **end** constitutes a block. Every declaration appears in a block in this way and is valid only for that block.

A program is a block or compound statement which is not contained within another statement and which makes no use of other statements not contained within it.

In the sequel the syntax and semantics of the language will be given.²

1.1. FORMALISM FOR SYNTACTIC DESCRIPTION

The syntax will be described with the aid of metalinguistic formulae.³ Their interpretation is best explained by an example

$$(ab) ::= (c) \mid (ab) \mid (cab)d$$

Sequences of characters enclosed in the brackets () represent metalinguistic variables whose values are sequences of symbols. The marks ::= and \mid (the latter with the meaning of **or**) are metalinguistic connectives. Any mark in a formula, which is not a variable or a connective, denotes itself (or the class of marks which are similar to it). Juxtaposition of marks and/or variables in a formula signifies juxtaposition of the sequences denoted. Thus the formula above gives a recursive rule for the formation of values of the variable (ab). It indicates that (ab) may have the value *c* or *[* or that given some legitimate value of (ab), another may be formed by following it with the character *c* or by following it with some value of the variable (d). If the values of (d) are the decimal digits, some values of (ab) are:

(c) (1-37)
(12345)
(
(86

In order to facilitate the study, the symbols used for distinguishing the metalinguistic variables (i.e. the sequences of characters appearing within the brackets () as *ab* in the above example) have been chosen to be words describing approximately the nature of the corresponding variable. Where words which have appeared in this manner are used elsewhere in the text they will refer to the corresponding syntactic definition. In addition some formulae have been given in more than one place.

Definition:

empty ::= ϵ
(i.e. the null string of symbols).

² Whenever the precision of arithmetic is stated as being in general not specified, or the outcome of a certain process is left undefined or said to be undefined, this is to be interpreted in the sense that a program only fully defines a computational process if the accompanying information specifies the precision assumed, the kind of arithmetic assumed, and the course of action to be taken in all such cases as may occur during the execution of the computation.

³ Cf. J. W. Backus, The syntax and semantics of the proposed international algebraic language of the Zürich ACM-GAMM conference, Proc. Internat. Conf. Inf. Proc., UNESCO, Paris, June 1959.

2. Basic Symbols, Identifiers, Numbers, and Strings. Basic Concepts.

The reference language is built up from the following basic symbols:

(basic symbol) ::= (letter) (digit) (logical value) (delimiter)

2.1. LETTERS

(letter) ::= *abcdefghijklmnopqrstuwxz*
ABCDEFGHIJKLMN OPQRSTU VWXYZ

This alphabet may arbitrarily be restricted, or extended with any other distinctive character (i.e. character not coinciding with any digit, logical value or delimiter).

Letters do not have individual meaning. They are used for forming identifiers and strings⁴ (cf. sections 2.4. Identifiers, 2.6. Strings).

2.2.1. DIGITS

(digit) ::= 0 1 2 3 4 5 6 7 8 9

Digits are used for forming numbers, identifiers, and strings.

2.2.2. LOGICAL VALUES

(logical value) ::= **true** **false**

The logical values have a fixed obvious meaning.

2.3. DELIMITERS

(delimiter) ::= (operator) (separator) (bracket) (declarator) (specifier)
(operator) ::= (arithmetic operator) (relational operator) (logical operator) (sequential operator)
(arithmetic operator) ::= + - * / ^
(relational operator) ::= < ≤ = ≥ > ≠
(logical operator) ::= ¬ ∩ ∪ ∩₁
(sequential operator) ::= **go to if then else for do**
(separator) ::= ; : () := **u step until while comment**
(bracket) ::= ([] { } **begin end**
(declarator) ::= **own Boolean integer real array switch; procedure**
(specifier) ::= **string label value**

Delimiters have a fixed meaning which for the most part is obvious or else will be given at the appropriate place in the sequel.

Typographical features such as blank space or change to a new line have no significance in the reference language. They may, however, be used freely for facilitating reading.

For the purpose of including text among the symbols of

⁴ It should be particularly noted that throughout the reference language underlining in typewritten copy; boldface type in printed copy (Ed.) is used for defining independent basic symbols (see sections 2.2.2 and 2.3). These are understood to have no relation to the individual letters of which they are composed. Within the present report [not including headings (Ed.)], boldface will be used for no other purpose.

⁵ **do** is used in for statements. It has no relation whatsoever to the *do* of the preliminary report, which is not included in ALGOL 60.

a program the following "concurrent" conventions hold:

The sequence of basic symbols: *is equivalent to*

<code>;</code>	<code>comment</code>	any sequence not containing <code>;</code>	<code>;</code>
<code>begin comment</code>	any sequence not containing <code>;</code>	<code>begin</code>	<code>begin</code>
<code>end</code>	any sequence not containing <code>end</code> or <code>;</code> or <code>else</code>	<code>end</code>	<code>end</code>

By equivalence is here meant that any of the three structures shown in the left hand column may be replaced, in any occurrence outside of strings, by the symbol shown on the same line in the right hand column without any effect on the action of the program. It is further understood that the comment structure encountered first in the text when reading from left to right has precedence in being replaced over later structures contained in the sequence.

2.4. IDENTIFIERS

2.4.1. Syntax

identifier ::= letter | identifier letter | identifier digit

2.4.2. Examples

```

q
Suip
U17a
a34kTMNs
MARILYN

```

2.4.3. Semantics

Identifiers have no inherent meaning, but serve for the identification of simple variables, arrays, labels, switches, and procedures. They may be chosen freely (cf., however, section 3.2.4. Standard Functions).

The same identifier cannot be used to denote two different quantities except when these quantities have disjoint scopes as defined by the declarations of the program (cf. section 2.7. Quantities, Kinds and Scopes, and section 5. Declarations).

2.5. NUMBERS

2.5.1. Syntax

unsigned integer ::= digit | unsigned integer digit
integer ::= unsigned integer | - unsigned integer
decimal fraction ::= . unsigned integer
exponent part ::= \pm integer
decimal number ::= unsigned integer / decimal fraction
 unsigned integer | decimal fraction
unsigned number ::= decimal number | exponent part |
 decimal number | exponent part
number ::= unsigned number | - unsigned number |
 unsigned number

2.5.2. Examples

0	-200.081	.083E-02
177	+07.43E8	-17
.5384	9.31E-10	1E-4
+0.7300	2E+4	1E+5

2.5.3. Semantics

Decimal numbers have their conventional meaning. The exponent part is a scale factor expressed as an integral power of 10.

2.5.4. Types

Integers are of type **integer**. All other numbers are of type **real** (cf. section 5.1. Type Declarations).

2.6. STRINGS

2.6.1. Syntax

proper string ::= any sequence of basic symbols not containing
' or ' empty
open string ::= (proper string | open string |
open string | open string
string ::= 'open string'

2.6.2. Examples

```

5k := '[" = ]T'
'. This u is u a u string'

```

2.6.3. Semantics

In order to enable the language to handle arbitrary sequences of basic symbols the string quotes ' and ' are introduced. The symbol **u** denotes a space. It has no significance outside strings.

Strings are used as actual parameters of procedures (cf. sections 3.2. Function Designators and 4.7. Procedure Statements).

2.7. QUANTITIES, KINDS AND SCOPES

The following kinds of quantities are distinguished: simple variables, arrays, labels, switches, and procedures.

The scope of a quantity is the set of statements and expressions in which the declaration of the identifier associated with that quantity is valid. For labels see section 4.1.3.

2.8. VALUES AND TYPES

A value is an ordered set of numbers (special case: a single number), an ordered set of logical values (special case: a single logical value), or a label.

Certain of the syntactic units are said to possess values. These values will in general change during the execution of the program. The values of expressions and their constituents are defined in section 3. The value of an array identifier is the ordered set of values of the corresponding array of subscripted variables (cf. section 3.1.4.1).

The various "types" (**integer**, **real**, **Boolean**) basically denote properties of values. The types associated with syntactic units refer to the values of these units.

3. Expressions

In the language the primary constituents of the programs describing algorithmic processes are arithmetic, Boolean, and designational expressions. Constituents of these expressions, except for certain delimiters, are logical values, numbers, variables, function designators, and elementary arithmetic, relational, logical, and sequential operators. Since the syntactic definition of both variables and function designators contains expressions, the definition of expressions, and their constituents, is necessarily recursive.

expression ::= arithmetic expression | Boolean expression |
designational expression

3.3.2. Examples

Primaries:

```
7.394 -8
sum
w2[i-2,8]
cos(y+z×3)
(a-3; y+va)8
```

Factors:

```
omega
sum*cos(y+z×3)
7.394 -8*w[i+2,8]*(a-3/y+va)8
```

Terms:

```
U
omega×sum*cos(y+z×3)/7.394 -8*w[i+2,8]
(a-3; y+va)8
```

Simple arithmetic expression:

```
V = Y a { omega×sum*cos(y+z×3)/7.394 -8*w[i+2,8]
(a-3; y+va)8 }
```

Arithmetic expressions:

```
w×a-Q(S+C)/2
if q>0 then S+3×Q/A else 2×S+3×q
if a<0 then U+V else if a×b>17 then U/V else if
k≠y then V/U else 0
a×sin(omega×t)
0.57v-12×a[N×(N-1)/2, 0]
(A×arctan(y)+Z)/(7+Q)
if q then n-1 else n
if a<0 then A/B else if b=0 then B/A else z
```

3.3.3. Semantics

An arithmetic expression is a rule for computing a numerical value. In case of simple arithmetic expressions this value is obtained by executing the indicated arithmetic operations on the actual numerical values of the primaries of the expression, as explained in detail in section 3.3.4 below. The actual numerical value of a primary is obvious in the case of numbers. For variables it is the current value (assigned last in the dynamic sense), and for function designators it is the value arising from the computing rules defining the procedure (cf. section 5.4.4. Values of Function Designators) when applied to the current values of the procedure parameters given in the expression. Finally, for arithmetic expressions enclosed in parentheses the value must through a recursive analysis be expressed in terms of the values of primaries of the other three kinds.

In the more general arithmetic expressions, which include if clauses, one out of several simple arithmetic expressions is selected on the basis of the actual values of the Boolean expressions (cf. section 3.4. Boolean Expressions). This selection is made as follows: The Boolean expressions of the if clauses are evaluated one by one in sequence from left to right until one having the value **true** is found. The value of the arithmetic expression is then the value of the first arithmetic expression following this Boolean (the largest arithmetic expression found in this position

is understood). The construction:

else (simple arithmetic expression)

is equivalent to the construction:

else if true then (simple arithmetic expression)

3.3.4. Operators and types

Apart from the Boolean expressions of if clauses, the constituents of simple arithmetic expressions must be of types **real** or **integer** (cf. section 5.1. Type Declarations). The meaning of the basic operators and the types of the expressions to which they lead are given by the following rules:

3.3.4.1. The operators $+$, $-$, and \times have the conventional meaning (addition, subtraction, and multiplication). The type of the expression will be **integer** if both of the operands are of **integer** type, otherwise **real**.

3.3.4.2. The operations (term) (factor) and (term) \div (factor) both denote division, to be understood as a multiplication of the term by the reciprocal of the factor with due regard to the rules of precedence (cf. section 3.3.5). Thus for example

$$a/b \times 7 / (p - q) \times r / s$$

means

$$(((a \times (b^{-1}) \times 7) \times (p - q)^{-1}) \times r) \times (s^{-1})$$

The operator \div is defined for all four combinations of types **real** and **integer** and will yield results of **real** type in any case. The operator \div is defined only for two operands both of type **integer** and will yield a result of type **integer**, mathematically defined as follows:

$$a \div b = \text{sign}(a/b) \times \text{entier}(\text{abs}(a/b))$$

(cf. sections 3.2.4 and 3.2.5).

3.3.4.3. The operation (factor) \uparrow (primary) denotes exponentiation, where the factor is the base and the primary is the exponent. Thus, for example,

$$2^*n \uparrow k \quad \text{means} \quad (2^n)^k$$

while

$$2^*(n \uparrow m) \quad \text{means} \quad 2^{n^m}$$

Writing i for a number of **integer** type, r for a number of **real** type, and a for a number of either **integer** or **real** type, the result is given by the following rules:

- $a \uparrow i$ If $i > 0$, $a \times a \times \dots \times a$ (i times), of the same type as a .
 If $i = 0$, if $a \neq 0$, 1, of the same type as a .
 If $a = 0$, undefined.
 If $i < 0$, if $a \neq 0$, $1/(a \times a \times \dots \times a)$ (the denominator has $-i$ factors), of type **real**.
 If $a = 0$, undefined.
- $a \uparrow r$ If $a > 0$, $\exp(r \times \ln(a))$, of type **real**.
 If $a \neq 0$, if $r > 0$, 0.0, of type **real**.
 If $r \leq 0$, undefined.
 If $a < 0$, always undefined.

3.3.5. Precedence of operators

The sequence of operations within one expression is

REVISED ALGOL 60

generally from left to right, with the following additional rules:

3.3.5.1. According to the syntax given in section 3.3.1 the following rules of precedence hold:

first: \wedge
 second: \times / \div
 third: $+ -$

3.3.5.2. The expression between a left parenthesis and the matching right parenthesis is evaluated by itself and this value is used in subsequent calculations. Consequently the desired order of execution of operations within an expression can always be arranged by appropriate positioning of parentheses.

3.3.6. Arithmetics of real quantities

Numbers and variables of type **real** must be interpreted in the sense of numerical analysis, i.e. as entities defined inherently with only a finite accuracy. Similarly, the possibility of the occurrence of a finite deviation from the mathematically defined result in any arithmetic expression is explicitly understood. No exact arithmetic will be specified, however, and it is indeed understood that different hardware representations may evaluate arithmetic expressions differently. The control of the possible consequences of such differences must be carried out by the methods of numerical analysis. This control must be considered a part of the process to be described, and will therefore be expressed in terms of the language itself.

3.4. BOOLEAN EXPRESSIONS

3.4.1. Syntax

relational operator ::= $< \leq = \geq > \neq$
 relation ::= (simple arithmetic expression)
 (relational operator (simple arithmetic expression))
 Boolean primary ::= (logical value) (variable)
 (function designator) (relation) (Boolean expression)
 Boolean secondary ::= (Boolean primary) \neg (Boolean primary)
 Boolean factor ::= (Boolean secondary)
 (Boolean factor) \wedge (Boolean secondary)
 (Boolean term) ::= (Boolean factor) (Boolean term)
 \vee (Boolean factor)
 (implication) ::= \rightarrow (Boolean term) (implication) \supset (Boolean term)
 (simple Boolean) ::= (implication)
 (simple Boolean) $=$ (implication)
 (Boolean expression) ::= (simple Boolean)
 (if clause (simple Boolean) **else** (Boolean expression))

3.4.2. Examples

```
x ← -2
Y > V ∨ z < q
a + b > -δ ∧ z - d > q2
p ∧ q ∨ x ≠ y
g = -a ∧ b ∧ -c ∨ d ∨ e ⊃ ¬ f
if k < 1 then s > w else h ≤ c
if if a then b else c then d else f then g else h < k
```

3.4.3. Semantics

A Boolean expression is a rule for computing a logical value. The principles of evaluation are entirely analogous to those given for arithmetic expressions in section 3.3.3.

3.4.4. Types

Variables and function designators entered as Boolean

primaries must be declared **Boolean** (cf. section 5.1, Type Declarations and section 5.4.4, Values of Function Designators).

3.4.5. The operators

Relations take on the value **true** whenever the corresponding relation is satisfied for the expressions involved, otherwise **false**.

The meaning of the logical operators \neg (not), \wedge (and), \vee (or), \supset (implies), and $=$ (equivalent), is given by the following function table.

b1	false	false	true	true
b2	false	true	false	true
\neg b1	true	true	false	false
b1 \wedge b2	false	false	false	true
b1 \vee b2	false	true	true	true
b1 \supset b2	true	true	false	true
b1 = b2	true	false	false	true

3.4.6. Precedence of operators

The sequence of operations within one expression is generally from left to right, with the following additional rules:

3.4.6.1. According to the syntax given in section 3.4.1 the following rules of precedence hold:

first: arithmetic expressions according to section 3.3.5.
 second: $< \leq = \geq > \neq$
 third: \neg
 fourth: \wedge
 fifth: \vee
 sixth: \supset
 seventh: $=$

3.4.6.2. The use of parentheses will be interpreted in the sense given in section 3.3.5.2.

3.5. DESIGNATIONAL EXPRESSIONS

3.5.1. Syntax

(label) ::= (identifier) (unsigned integer)
 (switch identifier) ::= (identifier)
 (switch designator) ::= (switch identifier) [(subscript expression)]
 (simple designational expression) ::= (label) (switch designator) [(designational expression)]
 (designational expression) ::= (simple designational expression) (if clause) (simple designational expression) **else** (designational expression)

3.5.2. Examples

```
17
p0
Choose[n-1]
Town if y < 0 then N else N+1
if Ab < c then 17 else q if w ≤ 0 then 2 else n
```

3.5.3. Semantics

A designational expression is a rule for obtaining a label of a statement (cf. section 4, Statements). Again the principle of the evaluation is entirely analogous to that of arithmetic expressions (section 3.3.3). In the general case the Boolean expressions of the if clauses will select a simple designational expression. If this is a label the desired result is already found. A switch designator refers to the corresponding switch declaration (cf. section 5.3,

Switch Declarations) and by the actual numerical value of its subscript expression selects one of the designational expressions listed in the switch declaration by counting these from left to right. Since the designational expression thus selected may again be a switch designator this evaluation is obviously a recursive process.

3.5.4. The subscript expression

The evaluation of the subscript expression is analogous to that of subscripted variables (cf. section 3.1.4.2). The value of a switch designator is defined only if the subscript expression assumes one of the positive values 1, 2, 3, ..., n , where n is the number of entries in the switch list.

3.5.5. Unsigned integers as labels

Unsigned integers used as labels have the property that leading zeros do not affect their meaning, e.g. 00217 denotes the same label as 217.

4. Statements

The units of operation within the language are called statements. They will normally be executed consecutively as written. However, this sequence of operations may be broken by go to statements, which define their successor explicitly, and shortened by conditional statements, which may cause certain statements to be skipped.

In order to make it possible to define a specific dynamic succession, statements may be provided with labels.

Since sequences of statements may be grouped together into compound statements and blocks the definition of statement must necessarily be recursive. Also since declarations, described in section 5, enter fundamentally into the syntactic structure, the syntactic definition of statements must suppose declarations to be already defined.

4.1. COMPOUND STATEMENTS AND BLOCKS

4.1.1. Syntax

```

<unlabelled basic statement> ::= <assignment statement>
    <go to statement> <dummy statement> <procedure statement>
<basic statement> ::= <unlabelled basic statement> <label>;
    <basic statement>
<unconditional statement> ::= <basic statement>;
<compound statement> <block>;
<statement> ::= <unconditional statement>
    <conditional statement> <for statement>;
<compound tail> ::= <statement> <end> <statement>;
    <compound tail>;
<block head> ::= <begin> <declaration> <block head>;
    <declaration>;
<unlabelled compound> ::= <begin> <compound tail>;
<unlabelled block> ::= <block head> <compound tail>;
<compound statement> ::= <unlabelled compound>;
    <label> <compound statement>;
<block> ::= <unlabelled block> <label> <block>;
<program> ::= <block> <compound statement>;

```

This syntax may be illustrated as follows: Denoting arbitrary statements, declarations, and labels, by the letters S, D, and L, respectively, the basic syntactic units take the forms:

Compound statement:

```
L: L; ... begin S ; S ; ... S ; S end
```

Block:

```
L: L; ... begin D ; D ; ... D ; S ; S ; ...S ;
    S end
```

It should be kept in mind that each of the statements S may again be a complete compound statement or block.

4.1.2. Examples

Basic statements:

```
a := p+q
go to Naples
START: CONTINUE: W := 7.993
```

Compound statement:

```
begin x := 0 ; for y := 1 step 1 until n do
    x := x+A[y] ;
if x>y then go to STOP else if x>w-2 then
    go to S ;
Aw: St: W := x+bob end
```

Block:

```
Q: begin integer i, k ; real w ;
    for i := 1 step 1 until m do
    for k := i+1 step 1 until m do
    begin w := A[i, k] ;
        A[i, k] := A[k, i] ;
        A[k, i] := w end for i and k
    end block Q
```

4.1.3. Semantics

Every block automatically introduces a new level of nomenclature. This is realized as follows: Any identifier occurring within the block may through a suitable declaration (cf. section 5. Declarations) be specified to be local to the block in question. This means (a) that the entity represented by this identifier inside the block has no existence outside it, and (b) that any entity represented by this identifier outside the block is completely inaccessible inside the block.

Identifiers (except those representing labels) occurring within a block and not being declared to this block will be nonlocal to it, i.e. will represent the same entity inside the block and in the level immediately outside it. A label separated by a colon from a statement, i.e. labelling that statement, behaves as though declared in the head of the smallest embracing block, i.e. the smallest block whose brackets **begin** and **end** enclose that statement. In this context a procedure body must be considered as if it were enclosed by **begin** and **end** and treated as a block.

Since a statement of a block may again itself be a block the concepts local and nonlocal to a block must be understood recursively. Thus an identifier, which is nonlocal to a block A, may or may not be nonlocal to the block B in which A is one statement.

4.2. ASSIGNMENT STATEMENTS

4.2.1. Syntax

```

<left part> ::= <variable> ::= <procedure identifier> ::=
<left part list> ::= <left part> <left part list> <left part>
<assignment statement> ::= <left part list> <arithmetic expression>;
    <left part list> <Boolean expression>;

```

REVISED ALGOL 60

4.2.2. Examples

```

s := p; V := n := n + 1; s
n := n + 1
A := B; C := q * S
N(p, k + 2) := 3 * arctan(s * zeta)
V := Q > Y / Z

```

4.2.3. Semantics

Assignment statements serve for assigning the value of an expression to one or several variables or procedure identifiers. Assignment to a procedure identifier may only occur within the body of a procedure defining the value of a function designator (cf. section 5.4.4). The process will in the general case be understood to take place in three steps as follows:

4.2.3.1. Any subscript expressions occurring in the left part variables are evaluated in sequence from left to right.

4.2.3.2. The expression of the statement is evaluated.

4.2.3.3. The value of the expression is assigned to all the left part variables, with any subscript expressions having values as evaluated in step 4.2.3.1.

4.2.4. Types

The type associated with all variables and procedure identifiers of a left part list must be the same. If this type is **Boolean**, the expression must likewise be **Boolean**. If the type is **real** or **integer**, the expression must be arithmetic. If the type of the arithmetic expression differs from that associated with the variables and procedure identifiers, appropriate transfer functions are understood to be automatically invoked. For transfer from **real** to **integer** type, the transfer function is understood to yield a result equivalent to

$$\text{entier}(E) + 0.5$$

where E is the value of the expression. The type associated with a procedure identifier is given by the declaration which appears as the first symbol of the corresponding procedure declaration (cf. section 5.4.4).

4.3. GO TO STATEMENTS

4.3.1. Syntax

/go to statement ::= go to designational expression

4.3.2. Examples

```

go to S
go to exit[n-1]
go to Tail if y < 0 then N else N + 1
go to if Ab < v then 17 else q if w < 0 then 2 else n

```

4.3.3. Semantics

A go to statement interrupts the normal sequence of operations, defined by the write up of statements, by defining its successor explicitly by the value of a designational expression. Thus the next statement to be executed will be the one having this value as its label.

4.3.4. Restriction

Since labels are inherently local, no go to statement can lead from outside into a block. A go to statement may, however, lead from outside into a compound statement.

4.3.5. Go to an undefined switch designator

A go to statement is equivalent to a dummy statement if the designational expression is a switch designator whose value is undefined.

4.4. DUMMY STATEMENTS

4.4.1. Syntax

(dummy statement) ::= empty

4.4.2. Examples

```

L:
begin ... ; Jahn; end

```

4.4.3. Semantics

A dummy statement executes no operation. It may serve to place a label.

4.5. CONDITIONAL STATEMENTS

4.5.1. Syntax

```

if clause ::= if Boolean expression then
unconditional statement ::= basic statement
compound statement ::= block
if statement ::= if clause / unconditional statement
conditional statement ::= if statement / if statement else
statement ::= if clause for statement
label ::= conditional statement

```

4.5.2. Examples

```

if x > 0 then a := a + 1
if x > a then V := q := a + a else go to R
if x < 0; P * Q then A, A; begin if q < r then a := r * s
else q := 2 * a end
else if x > s then a := r * q else if x > s + 1
then go to S

```

4.5.3. Semantics

Conditional statements cause certain statements to be executed or skipped depending on the running values of specified Boolean expressions.

4.5.3.1. If statement. The unconditional statement of an if statement will be executed if the Boolean expression of the if clause is true. Otherwise it will be skipped and the operation will be continued with the next statement.

4.5.3.2. Conditional statement. According to the syntax two different forms of conditional statements are possible. These may be illustrated as follows:

```
if B1 then S1 else if B2 then S2 else S3 ; S4
```

and

```
if B1 then S1 else if B2 then S2 else if B3 then S3 ; S4
```

Here B1 to B3 are Boolean expressions, while S1 to S3 are unconditional statements. S4 is the statement following the complete conditional statement.

The execution of a conditional statement may be described as follows: The Boolean expression of the if clauses are evaluated one after the other in sequence from left to right until one yielding the value **true** is found. Then the unconditional statement following this Boolean is executed. Unless this statement defines its successor explicitly the next statement to be executed will be S4, i.e. the state

ment following the complete conditional statement. Thus the effect of the delimiter **else** may be described by saying that it defines the successor of the statement it follows to be the statement following the complete conditional statement.

The construction


```
else (unconditional statement)
```

is equivalent to

```
else if true then (unconditional statement)
```

If none of the Boolean expressions of the if clauses is true, the effect of the whole conditional statement will be equivalent to that of a dummy statement.

For further explanation the following picture may be useful:



4.5.4. Go to into a conditional statement

The effect of a go to statement leading into a conditional statement follows directly from the above explanation of the effect of **else**.

4.6. FOR STATEMENTS

4.6.1. Syntax


```
(for list element) ::= (arithmetic expression)
(arithmetic expression) step (arithmetic expression) until
(arithmetic expression) (arithmetic expression) while
(Boolean expression)
(for list) ::= (for list element) (for list) ; (for list element)
(for clause) ::= for (variable) ::= (for list) do
(for statement) ::= (for clause) (statement)
label ::= for statement
```

4.6.2. Examples

```
for q := 1 step 2 until n do A[q] := B[q]
for k := 1, V1 × 2 while V1 < N do
  for j := 1 + G, L, 1 step 1 until X, C + D do
    A[k, j] := B[k, j]
```

4.6.3. Semantics

A for clause causes the statement S which it precedes to be repeatedly executed zero or more times. In addition it performs a sequence of assignments to its controlled variable. The process may be visualized by means of the following picture:



In this picture the word initialize means: perform the first assignment of the for clause. Advance means: perform the next assignment of the for clause. Test determines if the last assignment has been done. If so, the execution con-

tinues with the successor of the for statement. If not, the statement following the for clause is executed.

4.6.4. The for list elements

The for list gives a rule for obtaining the values which are consecutively assigned to the controlled variable. This sequence of values is obtained from the for list elements by taking these one by one in the order in which they are written. The sequence of values generated by each of the three species of for list elements and the corresponding execution of the statement S are given by the following rules:

4.6.4.1. Arithmetic expression. This element gives rise to one value, namely the value of the given arithmetic expression as calculated immediately before the corresponding execution of the statement S.

4.6.4.2. Step-until-element. An element of the form A **step** B **until** C, where A, B, and C, are arithmetic expressions, gives rise to an execution which may be described most concisely in terms of additional ALGOL statements as follows:

```
V := A ;
L1: if (V - C) × sign(B) > 0 then go to element exhausted ;
statement S ;
V := V + B ;
go to L1 ;
```

where V is the controlled variable of the for clause and *element exhausted* points to the evaluation according to the next element in the for list, or if the step-until-element is the last of the list, to the next statement in the program.

4.6.4.3. While-element. The execution governed by a for list element of the form E **while** F, where E is an arithmetic and F a Boolean expression, is most concisely described in terms of additional ALGOL statements as follows:

```
L3: V := E ;
if ¬F then go to element exhausted ;
Statement S ;
go to L3 ;
```

where the notation is the same as in 4.6.4.2 above.

4.6.5. The value of the controlled variable upon exit

Upon exit out of the statement S (supposed to be compound) through a go to statement the value of the controlled variable will be the same as it was immediately preceding the execution of the go to statement.

If the exit is due to exhaustion of the for list, on the other hand, the value of the controlled variable is undefined after the exit.

4.6.6. Go to leading into a for statement

The effect of a go to statement, outside a for statement, which refers to a label within the for statement, is undefined.

4.7. PROCEDURE STATEMENTS

4.7.1. Syntax

```
(actual parameter) ::= (string) (expression) (array identifier)
(switch identifier) (procedure identifier)
(letter string) ::= (letter) (letter string) (letter)
```

REVISED ALGOL 60

(parameter delimiter) ::= $\langle \rangle$ -letter string $\langle \rangle$
 (actual parameter list) ::= (actual parameter)
 (actual parameter list) (parameter delimiter)
 (actual parameter)
 (actual parameter part) ::= (empty) ;
 (actual parameter list) ;
 (procedure statement) ::= (procedure identifier)
 (actual parameter part)

4.7.2. Examples

Spur (1:Order; 6:Result to; 1)
Transpose (W; 1)
Absorb (A, X, M, Y; L, K)
InverseProduct (A, B, P, q; B, P, 10, P, Y)

These examples correspond to examples given in section 5.4.2.

4.7.3. Semantics

A procedure statement serves to invoke (call for) the execution of a procedure body (cf. section 5.4. Procedure Declarations). Where the procedure body is a statement written in ALGOL, the effect of this execution will be equivalent to the effect of performing the following operations on the program at the time of execution of the procedure statement:

4.7.3.1. Value assignment (call by value)

All formal parameters quoted in the value part of the procedure declaration heading are assigned the values (cf. section 2.8. Values and Types) of the corresponding actual parameters, these assignments being considered as being performed explicitly before entering the procedure body. The effect is as though an additional block embracing the procedure body were created in which these assignments were made to variables local to this fictitious block with types as given in the corresponding specifications (cf. section 5.4.5). As a consequence, variables called by value are to be considered as nonlocal to the body of the procedure, but local to the fictitious block (cf. section 5.4.3).

4.7.3.2. Name replacement (call by name)

Any formal parameter not quoted in the value list is replaced, throughout the procedure body, by the corresponding actual parameter, after enclosing this latter in parentheses wherever syntactically possible. Possible conflicts between identifiers inserted through this process and other identifiers already present within the procedure body will be avoided by suitable systematic changes of the formal or local identifiers involved.

4.7.3.3. Body replacement and execution

Finally the procedure body, modified as above, is inserted in place of the procedure statement and executed. If the procedure is called from a place outside the scope of any nonlocal quantity of the procedure body the conflicts between the identifiers inserted through this process of body replacement and the identifiers whose declarations are valid at the place of the procedure statement or function designator will be avoided through suitable systematic changes of the latter identifiers.

4.7.4. Actual-formal correspondence

The correspondence between the actual parameters of

the procedure statement and the formal parameters of the procedure heading is established as follows: The actual parameter list of the procedure statement must have the same number of entries as the formal parameter list of the procedure declaration heading. The correspondence is obtained by taking the entries of these two lists in the same order.

4.7.5. Restrictions

For a procedure statement to be defined it is evidently necessary that the operations on the procedure body defined in sections 4.7.3.1 and 4.7.3.2 lead to a correct ALGOL statement.

This imposes the restriction on any procedure statement that the kind and type of each actual parameter be compatible with the kind and type of the corresponding formal parameter. Some important particular cases of this general rule are the following:

4.7.5.1. If a string is supplied as an actual parameter in a procedure statement or function designator, whose defining procedure body is an ALGOL 60 statement (as opposed to non-ALGOL code, cf. section 4.7.8), then this string can only be used within the procedure body as an actual parameter in further procedure calls. Ultimately it can only be used by a procedure body expressed in non-ALGOL code.

4.7.5.2. A formal parameter which occurs as a left part variable in an assignment statement within the procedure body and which is not called by value can only correspond to an actual parameter which is a variable (special case of expression).

4.7.5.3. A formal parameter which is used within the procedure body as an array identifier can only correspond to an actual parameter which is an array identifier of an array of the same dimensions. In addition if the formal parameter is called by value the local array created during the call will have the same subscript bounds as the actual array.

4.7.5.4. A formal parameter which is called by value cannot in general correspond to a switch identifier or a procedure identifier or a string, because these latter do not possess values (the exception is the procedure identifier of a procedure declaration which has an empty formal parameter part (cf. section 5.4.1) and which defines the value of a function designator (cf. section 5.4.1). This procedure identifier is in itself a complete expression).

4.7.5.5. Any formal parameter may have restrictions on the type of the corresponding actual parameter associated with it (these restrictions may, or may not, be given through specifications in the procedure heading). In the procedure statement such restrictions must evidently be observed.

4.7.6. Deleted.**4.7.7. Parameter delimiters**

All parameter delimiters are understood to be equivalent. No correspondence between the parameter delimiters used in a procedure statement and those used in the procedure heading is expected beyond their number being the

same. Thus the information conveyed by using the elaborate ones is entirely optional.

4.7.8. Procedure body expressed in code

The restrictions imposed on a procedure statement calling a procedure having its body expressed in non-ALGOL code evidently can only be derived from the characteristics of the code used and the intent of the user and thus fall outside the scope of the reference language.

5. Declarations

Declarations serve to define certain properties of the quantities used in the program, and to associate them with identifiers. A declaration of an identifier is valid for one block. Outside this block the particular identifier may be used for other purposes (cf. section 4.1.3).

Dynamically this implies the following: at the time of an entry into a block (through the **begin**, since the labels inside are local and therefore inaccessible from outside) all identifiers declared for the block assume the significance implied by the nature of the declarations given. If these identifiers had already been defined by other declarations outside they are for the time being given a new significance. Identifiers which are not declared for the block, on the other hand, retain their old meaning.

At the time of an exit from a block (through **end**, or by a **go to** statement) all identifiers which are declared for the block lose their local significance.

A declaration may be marked with the additional declarator **own**. This has the following effect: upon a re-entry into the block, the values of own quantities will be unchanged from their values at the last exit, while the values of declared variables which are not marked as own are undefined. Apart from labels and formal parameters of procedure declarations and with the possible exception of those for standard functions (cf. sections 3.2.4 and 3.2.5), all identifiers of a program must be declared. No identifier may be declared more than once in any one block head.

Syntax.

```
(declaration) ::= (type declaration)|(array declaration)|
                 (switch declaration)|(procedure declaration)
```

5.1. TYPE DECLARATIONS

5.1.1. Syntax

```
(type list) ::= (simple variable) |
                (simple variable) , (type list)
(type ::= real | integer | Boolean
 (local or own type) ::= (type){own (type)
 (type declaration) ::= (local or own type)(type list)
```

5.1.2. Examples

```
integer p,q,s
own Boolean Acnyl,n
```

5.1.3. Semantics

Type declarations serve to declare certain identifiers to represent simple variables of a given type. Real declared variables may only assume positive or negative values

including zero. Integer declared variables may only assume positive and negative integral values including zero. Boolean declared variables may only assume the values **true** and **false**.

In arithmetic expressions any position which can be occupied by a real declared variable may be occupied by an integer declared variable.

For the semantics of **own**, see the fourth paragraph of section 5 above.

5.2. ARRAY DECLARATIONS

5.2.1. Syntax

```
(lower bound) ::= (arithmetic expression)
(upper bound) ::= (arithmetic expression)
(bound pair) ::= (lower bound) : (upper bound)
(bound pair list) ::= (bound pair) | (bound pair list) , (bound pair)
(array segment) ::= (array identifier) [(bound pair list) |
                    (array identifier) , (array segment)
(array list) ::= (array segment) : (array list) , (array segment)
(array declaration) ::= array (array list) [(local or own type)
                    array (array list)
```

5.2.2. Examples

```
array a, b, c[7:m, 2:m], s[-2:10]
own integer array A[if c<0 then 2 else 1:20]
real array q[-7:-1]
```

5.2.3. Semantics

An array declaration declares one or several identifiers to represent multidimensional arrays of subscripted variables and gives the dimensions of the arrays, the bounds of the subscripts and the types of the variables.

5.2.3.1. Subscript bounds. The subscript bounds for any array are given in the first subscript bracket following the identifier of this array in the form of a bound pair list. Each item of this list gives the lower and upper bound of a subscript in the form of two arithmetic expressions separated by the delimiter **:**. The bound pair list gives the bounds of all subscripts taken in order from left to right.

5.2.3.2. Dimensions. The dimensions are given as the number of entries in the bound pair lists.

5.2.3.3. Types. All arrays declared in one declaration are of the same quoted type. If no type declarator is given the type **real** is understood.

5.2.4. Lower upper bound expressions

5.2.4.1 The expressions will be evaluated in the same way as subscript expressions (cf. section 3.1.4.2).

5.2.4.2. The expressions can only depend on variables and procedures which are nonlocal to the block for which the array declaration is valid. Consequently in the outermost block of a program only array declarations with constant bounds may be declared.

5.2.4.3. An array is defined only when the values of all upper subscript bounds are not smaller than those of the corresponding lower bounds.

5.2.4.4. The expressions will be evaluated once at each entrance into the block.

5.2.5. The identity of subscripted variables

The identity of a subscripted variable is not related to the subscript bounds given in the array declaration. How-

REVISED ALGOL 60

ever, even if an array is declared **own** the values of the corresponding subscripted variables will, at any time, be defined only for those of these variables which have subscripts within the most recently calculated subscript bounds.

5.3. SWITCH DECLARATIONS

5.3.1. Syntax

(switch list) ::= (designational expression)
 (switch list) ; (designational expression)
 (switch declaration) ::= **switch** (switch identifier) := (switch list)

5.3.2. Examples

```
switch S := S1; S2 if p, if p > 5 then S3 else S1
switch Q := p) x
```

5.3.3. Semantics

A switch declaration defines the set of values of the corresponding switch designators. These values are given one by one as the values of the designational expressions entered in the switch list. With each of these designational expressions there is associated a positive integer, 1, 2, ..., obtained by counting the items in the list from left to right. The value of the switch designator corresponding to a given value of the subscript expression (cf. section 3.5, Designational Expressions) is the value of the designational expression in the switch list having this given value as its associated integer.

5.3.4. Evaluation of expressions in the switch list

An expression in the switch list will be evaluated every time the item of the list in which the expression occurs is referred to, using the current values of all variables involved.

5.3.5. Influence of scopes

If a switch designator occurs outside the scope of a quantity entering into a designational expression in the switch list, and an evaluation of this switch designator selects this designational expression, then the conflicts between the identifiers for the quantities in this expression and the identifiers whose declarations are valid at the place of the switch designator will be avoided through suitable systematic changes of the latter identifiers.

5.4. PROCEDURE DECLARATIONS

5.4.1. Syntax

(formal parameter) ::= (identifier)
 (formal parameter list) ::= (formal parameter) |
 (formal parameter list (parameter delimiter)
 (formal parameter)
 (formal parameter part) ::= (empty) | (formal parameter list)
 (identifier list) ::= (identifier) | (identifier list) ; (identifier)
 (value part) ::= **value** (identifier list) ; | (empty)
 (specifier) ::= **string** (type) **array** ; **type array label switch** |
procedure (type **procedure**)
 (specification part) ::= (empty) (specifier) (identifier list) ; |
 (specification part) (specifier) (identifier list) ;
 (procedure heading) ::= (procedure identifier)
 (formal parameter part) ; (value part) (specification part)
 (procedure body) ::= (statement) ; (code)
 (procedure declaration) ::=
procedure (procedure heading) (procedure body) ;
 (type) **procedure** (procedure heading) (procedure body)

5.4.2. Examples (see also the examples at the end of the report)

```
procedure Spar(a) Order: (n) Result: (s) ; value n ;  

array a ; integer n ; real s ;  

begin integer k ;  

  s := 0 ;  

for k := 1 step 1 until n do s := s + a[k, k]  

end
```

```
procedure Transpose(a) Order: (n) ; value n ;  

array a ; integer n ;  

begin real w ; integer i, k ;  

for i := 1 step 1 until n do  

  for k := 1 + i step 1 until n do  

  begin w := a[i, k] ;  

    a[i, k] := a[k, i] ;  

    a[k, i] := w  

  end  

end Transpose
```

```
integer procedure Step (a) ; real a ;  

Step := a if 0 ≤ a ∧ a ≤ 1 then 1 else 0
```

```
procedure Absmax(a) size: (n, m) Result: (y) Subscripts: (i, k) ;  

comment The absolute greatest element of the matrix a,  

  of size n by m is transferred to y, and the subscripts of this  

  element to i and k ;  

array a ; integer n, m, i, k ; real y ;  

begin integer p, q ;  

  y := 0 ;  

for p := 1 step 1 until n do for q := 1 step 1 until m do  

if abs(a[p, q]) > y then begin y := abs(a[p, q]) ; i := p ;  

  k := q  

end end Absmax
```

```
procedure Innerproduct(a, b) Order: (l, p) Result: (y) ; value l ;  

integer k, p ; real y, a, b ;  

begin real s ;  

  s := 0 ;  

for p := 1 step 1 until k do s := s + a × b ;  

  y := s  

end Innerproduct
```

5.4.3. Semantics

A procedure declaration serves to define the procedure associated with a procedure identifier. The principal constituent of a procedure declaration is a statement or a piece of code, the procedure body, which through the use of procedure statements and/or function designators may be activated from other parts of the block in the head of which the procedure declaration appears. Associated with the body is a heading, which specifies certain identifiers occurring within the body to represent formal parameters. Formal parameters in the procedure body will, whenever the procedure is activated (cf. section 3.2, Function Designators and section 4.7, Procedure Statements) be assigned the values of or replaced by actual parameters. Identifiers in the procedure body which are not formal will be either local or nonlocal to the body depending on whether they are declared within the body or not. Those of them which are nonlocal to the body may well be local to the block in the head of which the procedure declaration appears. The procedure body always acts like a

block, whether it has the form of one or not. Consequently the scope of any label labelling a statement within the body or the body itself can never extend beyond the procedure body. In addition, if the identifier of a formal parameter is declared anew within the procedure body (including the case of its use as a label as in section 4.1.3), it is thereby given a local significance and actual parameters which correspond to it are inaccessible throughout the scope of this inner local quantity.

5.1.4. Values of function designators

For a procedure declaration to define the value of a function designator there must, within the procedure body, occur one or more explicit assignment statements with the procedure identifier in a left part; at least one of these must be executed, and the type associated with the procedure identifier must be declared through the appearance of a type declarator as the very first symbol of the procedure declaration. The last value so assigned is used to continue the evaluation of the expression in which the function designator occurs. Any occurrence of the procedure identifier within the body of the procedure other than in a left part in an assignment statement denotes activation of the procedure.

5.1.5. Specifications

In the heading a specification part, giving information about the kinds and types of the formal parameters by means of an obvious notation, may be included. In this part no formal parameter may occur more than once. Specifications of formal parameters called by value (cf. section 4.7.3.1) must be supplied and specifications of formal parameters called by name (cf. section 4.7.3.2) may be omitted.

5.1.6. Code as procedure body

It is understood that the procedure body may be expressed in non-ALGOL language. Since it is intended that the use of this feature should be entirely a question of hardware representation, no further rules concerning this code language can be given within the reference language.

Examples of Procedure Declarations:

EXAMPLE 1.

```

procedure euler (fel, sum, eps, tim) ; value eps, tim ;
integer tim ; real procedure fel ; real sum, eps ;
comment euler computes the sum of fel(i) for i from zero up to
infinity by means of a suitably refined euler transformation. The
summation is stopped as soon as tim times in succession the absolute
value of the terms of the transformed series are found to be
less than eps. Hence, one should provide a function fel with one
integer argument, an upper bound eps, and an integer tim. The
output is the sum sum. abs is particularly efficient in the case
of a slowly convergent or divergent alternating series ;
begin integer i, n, t := 0 ; array m[0:15] ; real mp, ds ;
i := n := t := 0 ; m[0] := fel(0) ; sum := m[0] / 2 ;
m into m; i := i + 1 ; ms := fel(i) ;
for k := 0 step 1 until n do
begin mp := (sum + m[k]) / 2 ; m[k] := ms ;
ms := mp end means ;

```

```

if (abs(ms) < abs(m[n])) ∧ (n < 15) then
begin ds := mn / 2 ; n := n + 1 ; m[n] :=
mn end accept
else ds := mn ;
sum := sum + ds ;
if abs(ds) < eps then t := t + 1 else t := 0 ;
if t < tim then go to nextterm
end euler

```

EXAMPLE 2.

```

procedure RK (x, y, n, FKT, eps, eta, xE, yE, h) ; value x, y ;
integer n ; Boolean h ; real eps, eta, xE ; array
y, yE ; procedure FKT ;
comment RK integrates the system  $y_k' = f_k(x, y_1, y_2, \dots, y_n)$ 
( $k=1, 2, \dots, n$ ) of differential equations with the method of Runge-
Kutta with automatic search for appropriate length of integration
step. Parameters are: The initial values  $x$  and  $y[k]$  for  $x$  and the un-
known functions  $y_k(x)$ . The order  $n$  of the system. The procedure
FKT( $x, y, n, z$ ) which represents the system to be integrated, i.e.
the set of functions  $f_k$ . The tolerance values eps and eta which
govern the accuracy of the numerical integration. The end of the
integration interval  $xE$ . The output parameter  $yE$  which repre-
sents the solution at  $x=xE$ . The Boolean variable h, which must
always be given the value true for an isolated or first entry into
RK. If however the functions  $y$  must be available at several mesh-
points  $x_0, x_1, \dots, x_n$ , then the procedure must be called repeatedly
(with  $x=x_0, xE=x_{k+1}$ , for  $k=0, 1, \dots, n-1$ ) and then the
later calls may occur with h=false which saves computing time.
The input parameters of FKT must be  $x, y, n$ , the output parameter
 $z$  represents the set of derivatives  $z[k]=f_k(x, y[1], y[2], \dots, y[n])$ 
for  $x$  and the actual  $y$ 's. A procedure comp enters as a nonlocal
identifier ;
begin
array z, y1, y2, y3[1:n] ; real x1, x2, x3, h ; Boolean out ;
integer k, j ; own real s, Hs ;
procedure RK1ST (x, y, h, xe, ye) ; real x, h, xe ; array
y, ye ;
comment RK1ST integrates one single RUNGE-KUTTA
with initial values  $x, y[k]$  which yields the output
parameters  $xe=x+h$  and  $ye[k]$ , the latter being the
solution at  $x_e$ . Important: the parameters  $n, FKT, z$ 
enter RK1ST as nonlocal entities ;

```

begin

```

array w[1:n], a[1:5] ; integer k, j ;
a[1] := a[2] := a[5] := h / 2 ; a[3] := a[4] := h ;
xe := x ;
for k := 1 step 1 until n do ye[k] := w[k] := y[k] ;
for j := 1 step 1 until 4 do
begin
FKT(xe, ar, n, z) ;
xe := x + a[j] ;
for k := 1 step 1 until n do
begin
w[k] := y[k] + a[j] × z[k] ;
y[k] := y[k] + a[j] × z[k] / 3

```

This RK program contains some new ideas which are related to ideas of S. GILL. A process for the step-by-step integration of differential equations on an automatic computing machine, [Proc. Camb. Phil. Soc. 47 (1951), 96]; and E. FRÖBERG, On the solution of ordinary differential equations with digital computing machines, Föreläsning, Sällsk. Lund, Förel. 20, 11 (1950), 136-152. It must be clear, however, that with respect to computing time and round-off errors it may not be optimal, nor has it actually been tested on a computer.

REVISED ALGOL 60

```

    end k
  end j
  end RK1ST ;
Begin of program:
  if fi then begin H := xE-x ; s := 0 end else H := Hs ;
  out := false ;
AA: if (x):2.01×H-xE>0)::(H>0) then
  begin Hs := H ; out := true ; H := (xE-x)/2
  end if ;
  RK1ST (x,y,2×H,x1,y1) ;
BB: RK1ST (x,y,H,x2,y2) ; RK1ST(x2,y2,H,x3,y3) ;
  for k := 1 step 1 until n do
    if comp(y1[k],y3[k],x1)>eps then go to CC ;

```

```

comment: comp(a,b,c) is a function designator, the value
of which is the absolute value of the difference of the
mantissae of a and b, after the exponents of these quantities
have been made equal to the largest of the exponents
of the originally given parameters a,b,c ;
x := x3 ; if out then go to DD ;
for k := 1 step 1 until n do y[k] := y3[k] ;
if s=5 then begin s := 0 ; H := 2×H end if ;
s := s+1 ; go to AA ;
CC: H := 0.5×H ; out := false ; x1 := x2 ;
for k := 1 step 1 until n do y[k] := y2[k] ;
go to BB ;
DD: for k := 1 step 1 until n do yE[k] := y3[k] ;
end RK

```

ALPHABETIC INDEX OF DEFINITIONS OF CONCEPTS AND SYNTACTIC UNITS

All references are given through section numbers. The references are given in three groups:

- def Following the abbreviation "def", reference to the syntactic definition (if any) is given.
- synt Following the abbreviation "synt", references to the occurrences in metalinguistic formulae are given. References already quoted in the def-group are not repeated.
- text Following the word "text", the references to definitions given in the text are given.

The basic symbols represented by signs other than underlined words (in typewritten copy; boldface in printed copy—Ed.) have been collected at the beginning.

The examples have been ignored in compiling the index.

- + , see: plus
- , see: minus
- × , see: multiply
- /, ÷ , see: divide
- ↑ , see: exponentiation
- <, ≤, =, ≥, >, ≠ , see: (relational operator)
- =, ⊃, ∨, ∧, → , see: (logical operator)
- , , see: comma
- . , see: decimal point
- 10 , see: ten
- :
- ;, see: colon
- ;, see: semicolon
- := , see: colon equal
- ␣ , see: space
- (), see: parentheses
- [], see: subscript brackets
- ' , see: string quotes
- (actual parameter), def 3.2.1, 4.7.1
- (actual parameter list), def 3.2.1, 4.7.1
- (actual parameter part), def 3.2.1, 4.7.1
- (adding operator), def 3.3.1
- alphabet, text 2.1
- arithmetic, text 3.3.6
- (arithmetic expression), def 3.3.1 synt 3, 3.1.1, 3.3.1, 3.4.1, 4.2.1, 4.6.1, 5.2.1 text 3.3.3
- (arithmetic operator), def 2.3 text 3.3.4
- array, synt 2.3, 5.2.1, 5.4.1
- array, text 3.1.4.1
- (array declaration), def 5.2.1 synt 5 text 5.2.3
- (array identifier), def 3.1.1 synt 3.2.1, 4.7.1, 5.2.1 text 2.8
- (array list), def 5.2.1
- (array segment), def 5.2.1
- (assignment statement), def 4.2.1 synt 4.1.1 text 1, 4.2.3
- (basic statement), def 4.1.1 synt 4.5.1
- (basic symbol), def 2
- begin, synt 2.3, 4.1.1
- (block), def 4.1.1 synt 4.5.1 text 1, 4.1.3, 5
- (block head), def 4.1.1
- Boolean, synt 2.3, 5.1.1 text 5.1.3
- (Boolean expression), def 3.4.1 synt 3, 3.3.1, 4.2.1, 4.5.1, 4.6.1 text 3.4.3
- (Boolean factor), def 3.4.1
- (Boolean primary), def 3.4.1
- (Boolean secondary), def 3.4.1
- (Boolean term), def 3.4.1
- (bound pair), def 5.2.1
- (bound pair list), def 5.2.1
- (bracket), def 2.3
- (code), synt 5.4.1 text 4.7.8, 5.4.6
- colon, synt 2.3, 3.2.1, 4.1.1, 4.5.1, 4.6.1, 4.7.1, 5.2.1
- colon equal :=, synt 2.3, 4.2.1, 4.6.1, 5.3.1
- comma, synt 2.3, 3.1.1, 3.2.1, 4.6.1, 4.7.1, 5.1.1, 5.2.1, 5.3.1, 5.4.1
- comment, synt 2.3
- comment convention, text 2.3
- (compound statement), def 4.1.1 synt 4.5.1 text 1
- (compound tail), def 4.1.1
- (conditional statement), def 4.5.1 synt 4.1.1 text 4.5.3
- (decimal fraction), def 2.5.1
- (decimal number), def 2.5.1 text 2.5.3
- decimal point ., synt 2.3, 2.5.1
- (declaration), def 5 synt 4.1.1 text 1, 5 (complete section)
- (declarator), def 2.3
- (delimiter), def 2.3 synt 2
- (designational expression), def 3.5.1 synt 3, 4.3.1, 5.3.1 text 3.5.3
- (digit), def 2.2.1 synt 2, 2.1.1, 2.5.1
- dimension, text 5.2.3.2
- divide / ÷, synt 2.3, 3.3.1 text 3.3.4.2
- do, synt 2.3, 4.6.1
- (dummy statement), def 4.4.1 synt 4.1.1 text 4.4.3
- else, synt 2.3, 3.3.1, 3.4.1, 3.5.1, 4.5.1 text 4.5.3.2
- (empty), def 1.1 synt 2.6.1, 3.2.1, 4.4.1, 4.7.1, 5.4.1
- end, synt 2.3, 4.1.1
- entire, text 3.2.5
- exponentiation ↑, synt 2.3, 3.3.1 text 3.3.4.3
- (exponent part), def 2.5.1 text 2.5.3
- (expression), def 3 synt 3.2.1, 4.7.1 text 3 (complete section)

- (factor), def 3.3.1
- false**, synt 2.2.2
- for**, synt 2.3, 4.6.1
- (for clause), def 4.6.1 text 4.6.3
- (for list), def 4.6.1 text 4.6.4
- (for list element), def 4.6.1 text 4.6.4.1, 4.6.4.2, 4.6.4.3
- (formal parameter), def 5.4.1 text 5.4.3
- (formal parameter list), def 5.4.1
- (formal parameter part), def 5.4.1
- (for statement), def 4.6.1 synt 4.1.1, 4.5.1 text 4.6 (complete section)
- (function designator), def 3.2.1 synt 3.3.1, 3.4.1 text 3.2.3, 5.4.4

- go to**, synt 2.3, 4.3.1
- (go to statement), def 4.3.1 synt 4.1.1 text 4.3.3

- (identifier), def 2.4.1 synt 3.1.1, 3.2.1, 3.5.1, 5.4.1 text 2.4.3
- (identifier list), def 5.4.1
- if**, synt 2.3, 3.3.1, 4.5.1
- (if clause), def 3.3.1, 4.5.1 synt 3.4.1, 3.5.1 text 3.3.3, 4.5.3.2
- (if statement), def 4.5.1 text 4.5.3.1
- (implication), def 3.4.1
- integer**, synt 2.3, 5.1.1 text 5.1.3
- (integer), def 2.5.1 text 2.5.4

- label**, synt 2.3, 5.4.1
- (label), def 3.5.1 synt 4.1.1, 4.5.1, 4.6.1 text 1, 4.1.3
- (left part), def 4.2.1
- (left part list), def 4.2.1
- (letter), def 2.1 synt 2, 2.4.1, 3.2.1, 4.7.1
- (letter string), def 3.2.4, 4.7.1
- local, text 4.1.3
- (local or own type), def 5.1.1 synt 5.2.1
- (logical operator), def 2.3 synt 3.4.1 text 3.4.5
- (logical value), def 2.2.2 synt 2, 3.4.1
- (lower bound), def 5.2.1 text 5.2.4

- minus —, synt 2.3, 2.5.1, 3.3.1 text 3.3.4.1
- multiply ×, synt 2.3, 3.3.1 text 3.3.4.1
- (multiplying operator), def 3.3.1

- nonlocal, text 4.1.3
- (number), def 2.5.1 text 2.5.3, 2.5.4

- (open string), def 2.6.1
- (operator), def 2.3
- own**, synt 2.3, 5.1.1 text 5, 5.2.5

- (parameter delimiter), def 3.2.1, 4.7.1 synt 5.4.1 text 4.7.7
- parentheses (), synt 2.3, 3.2.1, 3.3.1, 3.4.1, 3.5.1, 4.7.1, 5.4.1 text 3.3.5.2
- plus +, synt 2.3, 2.5.1, 3.3.1 text 3.3.4.1
- (primary), def 3.3.1
- procedure**, synt 2.3, 5.4.1
- (procedure body), def 5.4.1
- (procedure declaration), def 5.4.1 synt 5 text 5.4.3
- (procedure heading), def 5.4.1 text 5.4.3
- (procedure identifier) def 3.2.1 synt 3.2.1, 4.7.1, 5.4.1 text 4.7.5.4
- (procedure statement), def 4.7.1 synt 4.1.1 text 4.7.3
- (program), def 4.1.1 text 1
- (proper string), def 2.6.1

- quantity, text 2.7

- real**, synt 2.3, 5.1.1 text 5.1.3
- (relation), def 3.4.1 text 3.4.5
- (relational operator), def 2.3, 3.4.1

- scope, text 2.7
- semicolon ;, synt 2.3, 4.1.1, 5.4.1
- (separator), def 2.3
- (sequential operator), def 2.3
- (simple arithmetic expression), def 3.3.1 text 3.3.3
- (simple Boolean), def 3.4.1
- (simple designational expression), def 3.5.1
- (simple variable), def 3.1.1 synt 5.1.1 text 2.4.3
- space u, synt 2.3 text 2.3, 2.6.3
- (specification part), def 5.4.1 text 5.4.5
- (specifier), def 2.3
- (specifier), def 5.4.1
- standard function, text 3.2.4, 3.2.5
- (statement), def 4.1.1, synt 4.5.1, 4.6.1, 5.4.1 text 4 (complete section)
- statement bracket, see: **begin end**
- step**, synt 2.3, 4.6.1 text 4.6.4.2
- string**, synt 2.3, 5.4.1
- (string), def 2.6.1 synt 3.2.1, 4.7.1 text 2.6.3
- string quotes ' ', synt 2.3, 2.6.1, text 2.6.3
- subscript, text 3.1.4.1
- subscript bound, text 5.2.3.1
- subscript brackets [], synt 2.3, 3.1.1, 3.5.1, 5.2.1
- (subscripted variable), def 3.1.1 text 3.1.4.1
- (subscript expression), def 3.1.1 synt 3.5.1
- (subscript list), def 3.1.1
- successor, text 4
- switch**, synt 2.3, 5.3.1, 5.4.1
- (switch declaration), def 5.3.1 synt 5 text 5.3.3
- (switch designator), def 3.5.1 text 3.5.3
- (switch identifier), def 3.5.1 synt 3.2.1, 4.7.1, 5.3.1
- (switch list), def 5.3.1

- (term), def 3.3.1
- ten ∞ , synt 2.3, 2.5.1
- then**, synt 2.3, 3.3.1, 4.5.1
- transfer function, text 3.2.5
- true**, synt 2.2.2
- (type), def 5.1.1 synt 5.4.1 text 2.8
- (type declaration), def 5.1.1 synt 5 text 5.1.3
- (type list), def 5.1.1

- (unconditional statement), def 4.1.1, 4.5.1
- (unlabelled basic statement), def 4.1.1
- (unlabelled block), def 4.1.1
- (unlabelled compound), def 4.1.1
- (unsigned integer), def 2.5.1, 3.5.1
- (unsigned number), def 2.5.1 synt 3.3.1
- until**, synt 2.3, 4.6.1 text 4.6.4.2
- (upper bound), def 5.2.1 text 5.2.4

- value**, synt 2.3, 5.4.1
- value, text 2.8, 3.3.3
- (value part), def 5.4.1 text 4.7.3.1
- (variable), def 3.1.1 synt 3.3.1, 3.4.1, 4.2.1, 4.6.1 text 3.1.3
- (variable identifier), def 3.1.1

- while**, synt 2.3, 4.6.1 text 4.6.4.3

AL.7a.18

CHAPTER 7b

Features of ALGOL-60
which are changed in ALGOL-20

This section lists those aspects of the Report which do not hold for ALGOL-20. The section numbers refer to the Report and page numbers refer to this manual.

- 2.1 Only upper case letters are available.
- 2.2.2, 2.3 The basic symbols indicated by underlined identifiers in the reference language (boldface in the report) are replaced in Algol-20 by identifiers with the same spelling. These identifiers, which may not be used for any other purpose, are referred to as "reserved identifiers". In addition, certain other reserved identifiers have been added to Algol-20. See Chapter 2, page 3ff.
- 2.3 A change to a new line of input text has the same significance as a blank space (except that strings may not continue beyond the end of a line). See Chapter 6a.
- 2.3 The characters \supset and \div are not available. The characters \equiv , \times , \leq and \geq are available in different forms. See Chapter 2, page 2.
- 2.4 Identifiers may not contain spaces. However, see Chapter 2, page 5, for alternative punctuation.
- 2.5 See Chapter 2, page 6 for the range of values of meaningful numbers.
- 2.6.1 Since ALGOL-20 cannot distinguish between a left and right string quote, strings may not contain strings.
- 3.1.4.2 Array subscripts are truncated, not rounded, when they are evaluated.
- 3.3.4.2 \div is not available. See Chapter 2, page 2.
- 3.3.4.3 \uparrow produces a value of type real when it is applied to any combination of real and integer values.
- 3.4 \supset is not available. See Chapter 2, page 8.
- 3.4.6.1 \equiv has the same precedence as $=$.
- 3.5 A label may not be an unsigned integer.
- 4.1 ALGOL-20 defines $\langle \text{program} \rangle ::= \langle \text{unlabeled block} \rangle | \langle \text{unlabeled compound} \rangle$. Thus the first character of a program must be a begin.

AL.7b.2

4.1.3 If the first occurrence of a label in the block in which it is defined is as an actual parameter, it is necessary to declare it as a label in that block head.

4.6 The controlled variable in a for statement may only be a simple variable.

4.7.3.1 Arrays cannot be called by value.

5.2 Dynamic own arrays are not allowed.

5.4 Recursive procedures are not available.

5.4.5 All formal parameters must be specified.

CHAPTER 7c

Restrictions on ALGOL-20

to transform it into a subset of ALGOL-60

The user of ALGOL-20 may use many abilities which are not part of ALGOL-60, since the translator at Carnegie Tech implements an extension of the language. If a program (or procedure) is to be sent outside of Carnegie Tech, however, the programmer may wish to restrict himself to those aspects of our system which are part of the standard language. To do so, he must obey the rules given in this section.

Anything which gives a note (except for notes 1 and 2) indicates a deviation of ALGOL-20 from ALGOL-60 and so should not be used.

All left parts in a statement must be of the same type.

Boolean variables must not occur as primaries in arithmetic expressions.

Arithmetic variables must not occur as primaries in Boolean expressions.

Go must be followed by to.

Nothing may be assumed about the initial value of a variable - including own variables.

"." is not a legal character in identifiers.

Constants may not end with a decimal point.

Variables may only be of type real, integer or Boolean.

The value of a for variable is undefined after the for statement has run to completion.

If a unary operator follows another operator, it and its operand must usually be surrounded by parentheses.

None of the following exist in ALGOL-60 and must not be used:

octal constants

alphanumeric string constants

step..while for-list elements

privileged identifiers (with their privileged meanings)

label declarations

nested substitutions

the operators \downarrow and \leftarrow

the reserved words max, min, and mod

library procedures

SY statements

CO statements

WHAT

the operator = used to mean \equiv

input/output

|| comment convention

THIS PUBLICATION IS AVAILABLE AT:

THE BOOK STORE
BAKER HALL
CARNEGIE INSTITUTE OF TECHNOLOGY
PITTSBURGH, PENNSYLVANIA 15213

THE SALE PRICE (\$1.25)* REFLECTS THE COST
OF PRINTING AND DISTRIBUTION ONLY.

*(Add \$.06 sales tax for purchase in Pa.)
*(Add \$.20 postage for mail orders)

